

LSHC® 2.5V Series

Screw in terminal

Features and benefits



- Hybrid capacitor
- Long term reliable cycle life
- Quick charge & discharge available


Typical Application

- Consumer application
- Short term UPS
- Windmill pitch control
- Power back up
- Robotics memory back up
- Solar application



Physical properties

Dimension in mm (not to scale)



Specification

Rated Voltage	2.5 V	
Surge Voltage	2.7 V	
Capacitance Tolerance	-10% / 10%	
Resisistance Tolerance	MAX.	
Operating temperature range	-25 ~ 60 °C	
Storage temperature range	-25 ~ 70 °C	
Life Time (25°C)	After 10 years at rated voltage and +25 °C	
	Capacitance change	Within 30% of initially specified value
	Internal resistance change	Within 200% of initially specified value
Cycle Life (25°C)	After 500,000 cycles at +25 °C	
	Capacitance change	Within 30% of initially specified value
	Internal resistance change	Within 200% of initially specified value

* Operating voltage range : 2.5 ~ 1.0V

Standard Ratings

Capacitance (F)	Dimension (mm)			Resistance(mΩ)		Max. Current (A)	Leakage Current (mA)	Max. Stored Energy (Wh)	Weight (g)	Part number
	D	W	L	(100Hz)	DC					
5400	55	55	155	0.40	0.50	1,824	< 10	4.67	760	LSHC 002R5P 5400F EA

LS Ultracapacitors have been Certified by ISO/TS16949, ISO14001:2004, OHSAS18001:2007, UL

Your Power Solutions Spc Distributed by:



1573 Laperriere Ave. Ottawa ON K1Z 7T3
(613) 725-3704 www.cantecsystems.com

Design, Specifications may change without notice.

555, Hogye-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea, 431-831

Tel: 82-31-428-4545 Email: ultracapacitor@lsmtron.com

Copyright 2009 LS Mtron Ltd. All rights Reserved.