

# CANTEC MSC1210x5

5 BANK BATTERY CHARGER

## OVERVIEW

The MSC1210X5 Multi station is a fully automatic, smart battery charger which provides five (5) independent DC outputs for charging multiple batteries simultaneously. Each output has

its own status indicator for monitoring the individual battery. The 5X requires only a single AC power cord. The advanced 3-stage, proportionally timed charge program is designed to provide optimize charging performance of sealed batteries such as the Hawker & Optima. As soon as the battery is connected, a de-sulfation circuit encourages the breakdown of large sulfate crystals which can develop during prolonged periods of deep discharge.



## 5X FEATURES :

- Charge output programmed specifically for sealed military batteries.
- Can charge different brands/models of batteries simultaneously. Multi-step charge output for efficient full battery charging. Optimizes charge program based on individual battery condition.
- Temperature compensation, adjusts output voltage relevant to work area temperature. This prevents overcharge when it's hot, and ensures a full charge when it's cold.
- De-sulfation circuit encourages the breakdown of sulfate crystal formation on plates
- Automatic Short Circuit & Reverse Polarity Protection for enhanced safety.
- Safety/Fault protection shuts charger down when it detects certain battery problems. Easy to read LED battery status indicator on each output.
- Factory programmable for optimized charging of AGM, Flooded and Gel type batteries.

## SPECIFICATIONS

12 VOLT

Model:	12-volt, 5-bank charger
P/N:	MSC-1210x5
AC Input:	115VAC, 8 Amps or 230VAC, 4 amps
DC Output:	10 amps DC output per channel
Dimensions:	26"W, 6"D, 9"H
Weight:	48 lbs.

**Cantec**  
Systems

Your Power Solutions Specialists

1573 LAPERRIERE AVENUE OTTAWA ON K1Z 7T3

OTTAWA  
Tel: 613-725-3704  
Fax: 613-725-0490

TORONTO:  
Tel: 613-725-3704  
Fax: 613-725-0490

VANCOUVER:  
Tel: 604-736-4922  
Fax: 604-736-1074

A DIVISION OF CANTEC REPRESENTATIVES